



IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re application of: Paolo Salvoni

Group No.:

Serial No.: 10/826,566

Filed: April 16, 2004

Examiner:

For: MACHINE FOR SEALING CONTAINERS BY APPLYING A  
COVERING FILMCommissioner for Patents  
P.O. Box 1450  
Alexandria, VA 22313-1450

## TRANSMITTAL OF CERTIFIED COPY

Attached please find the certified copy of the foreign application from which priority is claimed for this case:

Country : EUROPE  
Application Number : 03010670.2  
Filing Date : 13 MAY 2003

**WARNING:** "When a document that is required by statute to be certified must be filed, a copy, including a photocopy or facsimile transmission of the certification is not acceptable." 37 CFR 1.4(h) (emphasis added.)

  
SIGNATURE OF ATTORNEY

Reg. No.: 44,004

Geza C. Ziegler, Jr.

Tel. No.: (203) 259-1800

Type or print name of attorney

Perman & Green, LLP

Customer No.: 2512

P.O. Address425 Post Road, Fairfield, CT 06824

NOTE: The claim to priority need be in no special form and may be made by the attorney or agent if the foreign application is referred to in the oath or declaration as required by ☐ 1.63.

(Transmittal of Certified Copy [5-4])

**THIS PAGE BLANK (USPTO)**



**Europäisches  
Patentamt**

**European  
Patent Office**

**Office européen  
des brevets**

**Bescheinigung**

**Certificate**

**Attestation**

Die angehefteten Unterlagen stimmen mit der ursprünglich eingereichten Fassung der auf dem nächsten Blatt bezeichneten europäischen Patentanmeldung überein.

The attached documents are exact copies of the European patent application described on the following page, as originally filed.

Les documents fixés à cette attestation sont conformes à la version initialement déposée de la demande de brevet européen spécifiée à la page suivante.

**Patentanmeldung Nr.    Patent application No.    Demande de brevet n°**

03010670.2

**CERTIFIED COPY OF  
PRIORITY DOCUMENT**

Der Präsident des Europäischen Patentamts;  
Im Auftrag

For the President of the European Patent Office

Le Président de l'Office européen des brevets  
p.o.

**R C van Dijk**

**THIS PAGE BLANK (USPTO)**



Anmeldung Nr:  
Application no.: 03010670.2  
Demande no:

Anmeldetag:  
Date of filing: 13.05.03  
Date de dépôt:

Anmelder/Applicant(s)/Demandeur(s):

CFS Palazzolo  
Via Piantada No. 8  
25036 Palazzolo (BS)  
ITALIE

Bezeichnung der Erfindung/Title of the invention/Titre de l'invention:  
(Falls die Bezeichnung der Erfindung nicht angegeben ist, siehe Beschreibung.  
If no title is shown please refer to the description.  
Si aucun titre n'est indiqué se référer à la description.)

Machine for sealing containers by applying a covering film

In Anspruch genommene Priorität(en) / Priority(ies) claimed /Priorité(s)  
revendiquée(s)

Staat/Tag/Aktenzeichen/State/Date/File no./Pays/Date/Numéro de dépôt:

EP/17.04.03/EP 03008981

Internationale Patentklassifikation/International Patent Classification/  
Classification internationale des brevets:

B65B/

Am Anmeldetag benannte Vertragstaaten/Contracting states designated at date of  
filing/Etats contractants désignées lors du dépôt:

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LU MC NL  
PT RO SE SI SK TR LI

**THIS PAGE BLANK (USPTO)**

CI0113EP/A

**Machine for sealing containers by applying a covering film**

The present invention is related to a machine for sealing containers by applying a covering film or a lid.

These machines are known from the state in the art. For these machines, it is necessary that several containers are located with a certain gap pattern, for example equidistantly, on an accumulation conveyor, before they are grabbed by a pusher arm, which transports the container to the sealing unit, where a film is applied to the containers. EP 0 680 880 for example describes a feeder unit which allows the equidistant accumulation of containers on the accumulation belt. The feeder unit comprises an accumulation conveyor, a feeder conveyor and at least one buffer conveyor which is interposed between the accumulation conveyor and the feeder conveyor. With the buffer conveyor it is assured that the containers are handed over to the accumulation conveyor at a pre set speed and at a pre set position. The containers are grabbed by the pusher arm while they are moved by the accumulation conveyor. This system works well, but is relatively complicated.

It is therefore the objection of the present invention to provide a machine for sealing containers, which does not have the disadvantages of the state of the art.

The problem is solved by a machine according to claim 1. Preferred features of the inventive machine are claimed in the dependent claims 2 -7.

It was totally surprising and could not have been expected by a person skilled in the art that the inventive machine allows to space containers equidistantly on an accumulation belt which are randomly positioned on a feeder conveyor with very simple means. The inventive machine is operated easily and needs little maintenance.

The inventive machine for sealing containers has a container sealing unit, which applies a covering film on the containers. Additionally, the machine has a unit for feeding the containers to the sealing unit, which comprises an accumulation conveyor which is located upstream of the sealing unit and a feeder conveyor which

feeds the containers to the accumulation conveyor. Both conveyors are driven by motor means. Additionally, the inventive machine comprises a first sensor which is preferably located in the end zone of the feeder conveyor and which detects the containers on the feeder conveyor, preferably their front edge. The speed of motion of the feeder conveyor is also detected by detection means and/or the speed is maintained constant. The first sensor and the detection means are connected to a control unit which controls the motor means of the accumulation conveyor such that the correct gap between two adjacent containers on the accumulation conveyor is achieved and that the speed of the accumulation conveyor and the speed of the feeder conveyor are synchronised during the handing over of the containers from the feeder conveyor to the accumulation conveyor. If the speed of the feeder conveyor is maintained constant, no speed detection means are needed, but the control unit must have the information about the magnitude speed of the feeder conveyor.

Preferably, the machine comprises a second sensor which is located upstream of the first sensor and which detects the distance between two containers on the feeder conveyor. The second sensor is preferable also connected to the control unit which also control the motor means of the feeder conveyor. If the distance between two trays on the feeder conveyors is significantly smaller than the desired gap, the control unit reduces temporarily the speed of the feeder conveyor and/or it temporarily stops the backtray via a technical mean, preferably a mechanical mean.

The motor means of the accumulation- and/or the feeder conveyor can be any motor known by a person skilled in the art. However a servomotor for the feeder conveyor and a motor with full rotation intelligent control via an electronic cam are preferred.

The inventive machine comprises additionally pusher arms which can be detachably associated with multiple containers on the accumulation conveyor to transfer the containers to the sealing unit and from the sealing unit to a conveyor, which is located downstream of the sealing unit for removing the sealed containers from the inventive machine.



Further characteristics and advantages will become apparent from the following detailed description of Figures 1 – 4, which are, however, not limitative examples of the present invention.

Figure 1 shows one embodiment of the infeed system of the inventive machine.

Figure 2 shows a machine with two sensors.

Figure 3 shows an infeed system with an external feeder conveyor.

Figure 4 shows another infeed system with an external feeder conveyor.

Figure 1 shows the unit 2 for feeding containers to be sealed to the sealing unit (not shown). The unit 2 comprises an accumulation conveyor 3 and a feeder conveyor 4. The direction of motion of the containers is indicated by the arrow. In the present example, the feeder conveyor 4 is an endless belt. The feeder conveyor 4 comprises a sensor 5 which detects the front edge 7 of the containers 1. The feeder conveyor 4 is driven continuously by a motor 13. Additionally, the feeder conveyor comprises detection means 9 to detect the speed of motion of the feeder conveyor 4. Alternatively, it is possible to operate the feeder conveyor 4 at a constant speed. Then the detection means 9 are not needed. The signal of the sensor 5 and the signal of the detection means 9 or the desired constant speed are transferred to a control unit that controls motor means 8, which drives the accumulation belt. Based on these signal of the sensor 5 and the information about the speed of the feeder conveyor 4, the control unit controls the motor 8 such that the correct gap between two adjacent containers is created on the accumulation conveyor and that the speed of the accumulation conveyor and the feeder conveyor are synchronised during the handing over of the containers 1 from the feeder conveyor 4 to the accumulation conveyor 3. This is done as follows:

The accumulation conveyor stands still until sensor 5 detects a new tray. Based on the desired gap 11, motor means 8 accelerate the accumulation conveyor 3 faster or slower until the accumulation conveyor 3 has reached a velocity related to the feeder conveyor 4, preferably equal to the speed of the feeder conveyor. This process is

controlled by a control unit (not shown). This velocity of the accumulation conveyor 3 is then preferably maintained until the container has at least partially been handed over from the feeder conveyor 4 to the accumulation conveyor 3. After this handing over, the accumulation belt 3 is decelerated again until it comes to a stop. The rate of deceleration is also based on the size of the desired gap 11. The person skilled in the art understands that the accumulation belt needs not come to complete stop after each positioning of a container. Only if one set of containers 1 on the accumulation conveyor 3 is completed, the accumulation conveyor 3 comes to a complete stop and two pusher arms (not depicted) grab the containers and feed them to the sealing unit (not depicted).

**Figure 2** shows the unit 2 for feeding containers to be sealed according to figure 1 but with an additional sensor 10 which is located upstream of sensor 5. This sensor 10 measures the distance 12 between two containers 1 and 1' on the feeder conveyor 4. If this distance 12 is smaller than the minimum gap needed for the handover of tray 1 before tray 1' is coming to the handover position as well, the control unit slows down motor 13 of the feeder conveyor 4 to give the accumulation conveyor 3 enough time to increase the distance between tray 1 and 1', before tray 1' is in the handover position to the accumulation conveyor. This increases the distance between containers 1 and 1', so that the control unit is able to maintain the desired gaps 11. Alternatively or in combination with the above mentioned control scheme a mechanical mean can temporarily slow down the tray 1' in order to increase the gap between 1 and 1'.

**Figure 3** shows the system according to figure 2 which additionally comprises an external feeder conveyor 14 which operates at continuous or random speed. This conveyor is not necessarily controlled by the control unit.

**Figure 4** shows a system according to figure 3, whereas the external feeder conveyor 14 is in the present example a chain with pushers 15.

**List of reference numbers:**

- 1, 1' containers
- 2 unit for feeding containers
- 3 accumulation conveyor
- 4 feeder conveyor
- 5 first sensor
- 6 end-zone of the feeder conveyor
- 7 front edge of the container
- 8 motor means
- 9 detection means
- 10 second sensor
- 11 desired gap
- 12 random distance between two trays
- 13 motor means
- 14 external feeder conveyor
- 15 pusher

CI0113EP/A

**Claims:**

1. Machine for sealing containers (1) with a container sealing unit, which is located after a unit (2) for feeding containers to be sealed, which comprises an accumulation conveyor (3) located upstream of the sealing unit and driven by motor means (8) and a feeder conveyor (4), which feeds containers to the accumulation conveyor (3) and driven by motor means (13), characterized in that it further comprises a first sensor (5) preferably in the end-zone (6) of the conveyor (4), detecting, preferably the front edge (7), of the container (1) and preferably detection means (9) to detect the speed of motion of the feeder conveyor (4) and that the first sensor (5) and preferably the detection means (9) are connected to a control unit, which controls the motor means (8) such that the desired gap (11) is created between two adjacent containers (1) on the accumulation conveyor (3) and that the speed of the accumulation conveyor (3) and of the feeder conveyor (4) are synchronized during at least a partial handing over of the containers (1) from the feeder conveyor (4) to the accumulation conveyor (3).
2. Machine according to claim 1, characterized in, that comprises a second sensor (10) upstream of the first sensor, which detects the distance (12) between two containers on the feeder conveyor (4).
3. Machine according to claim 2 characterized in, that the second sensor (10) is connected to the control unit, which reduces the speed of the feeder conveyor (4) if the distance (12) of two containers on the feeder conveyor (4) is significantly smaller than the minimum gap needed for the handover of tray 1 before tray 1 is coming to the handover position as well.
4. Machine according to anyone of the preceding claims, characterized in, that the motor means (8, 13) are servo motors.
5. Machine according to claim 1, characterized in, that the feeder conveyor (4) operates at continuous or random speed.

CI0113EP/A


6. Machine according to anyone of the preceding claims, characterized in, that it comprises pusher arms, which can be detachably associated with multiple containers on the accumulation conveyor (3) to transfer the containers (1) to the sealing unit.
7. Machine according to claim 6, characterized in, that the transfer is carried out while the accumulation conveyor (3) stands still.

### **Summary**


The present invention is related to a mean machine for sealing containers by applying a covering film or a lid.

CI0113EP/A

C1013EP/A




CIOMBER/A





C10M3EP/A



C10113EP/A

